

HFX Singlephase 230Vac - Up to 1050W - 12/24V, 36V, 48V

CODING (example)

MODEL	V	A	CURVE code
▼	▼	▼	▼
HFXD	12 -- 24	30	P00


SUITABLE BATTERIES

Lead acid - PzS
 GEL - AGM - VRLA - PzV
 Lithium - (on demand)

EXPECTED RECHARGE TIME

7-13,5h

MAIN APPLICATIONS



HFX



DOUBLE VOLTAGE
12/24V



ON BOARD
FEATURES



LAPTOP
SET / DATA STORAGE



SWITCH
PROFILES
SELECTION

PRODUCT INTRO

HFX is the small-medium sized HF charger suitable for semi-traction & on-board applications with LED visual interface. Easy built-in jumpers enable Voltage and Profile selection (12-24V and WET-GEL*) including a PC connection for advanced setting, data-report and diagnostic.

(* default setting; profile 2 is customizable upon request or selected via PC).

MODELS AVAILABLE

V	A	VAC	CODE	Ah in 7-8,5h*	Ah in 11-13,5h*	cabinet code
12 -- 24	25	1x230	HFXD 12-24/ 25	116-173	235-282	2
12 -- 24	30	1x230	HFXD 12-24/ 30	137-203	277-332	2
36	20	1x230	HFXD 36/ 20	91-136	185-222	2
48	15	1x230	HFXD 48/ 15	71-105	143-171	2

*Ah referred to lead acid batteries

GENERAL CHARACTERISTICS

General information	High Frequency charger - Switching technology
Visual Signalling	Single LED (3 colours) on the front side
External Signalling (optional)	Single LED (3 colours)
Charger setting	(by DIPs) Voltage (12-24) and Charging Profile (0-1) (by PC) 7 preset charging profiles, Ah, output current
Switch (on-off)	Present (near to the input cable)
Storage Data	Charger gives a Report of the last 25 charges and other information (by PC)
Operating Temperature	-0 to +40° full power +55°C with derating
Storage Temperature	-5 to +40°
Max Humidity	RH 90% without condensation

ELECTRICAL CHARACTERISTICS AND SAFETIES

Mains	Vac 230V (1ph) +/-10% 50-60Hz
Efficiency	>85%
Input Protection	Delay Fuse
Output Protection	By Relay (reverse polarity protection)
Thermal Protections	A probe on primary side forces a derating (fix value) A probe on the diodes forces a derating or stops charging if needed (can be set)
Insulation	2 kV
Output short circuit	Protected (by undervoltage) Chargers shut down in few seconds
Opening Output Cables	Protected (by undervoltage) Chargers shut down in few seconds

OPTIONALS

On board	Inhibitor cable - Vac presence relay
On board	Remote Led
On board	Curly cable
Stand alone / wall mounted	Cable holder
On board / stand alone / wall	Thermal coating

MECHANICAL CHARACTERISTICS

Dimension	248 (L-body) 112 (W) 75(h) 275 (L- plate) mm.
Wall mounting	50x260 mm
Protection Degree	IP20 (vertical) IP21 (horizontal)
Installation requirements	Forced ventilation charger. Do not cover air openings (distance 300mm typ.)
Weight	1,88 Kg (without cables); 2,55 Kg (with std cables)
Input cable length	2.350 mm (length)
Input Plug	Schuko 16A/250V (CEE 7/7)
Output cable	2.400 mm (length)
Output Plug	Optional

MAIN CHARGING PROFILES AVAILABLE

IUa
IUoU
IUIa
IUIU
on demand

